



Material Safety Data Sheet

WHMIS (Pictograms)	WHMIS (Classification)	Protective Clothing
	Class B-2: Flammable liquid with a flash point lower than 37.8°C (100°F).	

Section 1. Chemical Product and Company Identification	
Product Name/ Trade name	Topcoat PU Satin (M57-15)
Supplier	Antoni Coatings Inc. 2910 Marleau Avenue P.O. Box 1236 Cornwall, Ontario K6H 5V3
Synonym	Not available.
Chemical Name	Not applicable.
Chemical Family	Not applicable.
Chemical Formula	Not applicable.
Manufacturer	Milesi S.P.A. Via Varese, 2 20010 Bareggio Milano, Italy
Material Uses	Not available.
Code	LGA23
CAS #	Mixture.
DSL	CEPA DSL: Toluene; Glycol Ether PM Acetate; Xylene
CI#	Not applicable.
Validation Date	1/03/2007
Print Date	1/03/2007
In Case of Emergency	Canutec: (613) 996-6666

Section 2. Composition and Information on Ingredients				
Name	CAS #	% by Weight	Exposure Limits	LC ₅₀ /LD ₅₀
1) Toluene	108-88-3	10-25	TWA: 200 (ppm) from OSHA (PEL) [United States] TWA: 50 (ppb) from ACGIH (TLV) [United States] TWA: 188 (ppm) from ACGIH TWA: 100 STEL: 150 (ppm) from NIOSH	ORAL (LD50): Acute: 2600 mg/kg [Rat]. DERMAL (LD50): Acute: 12210 mg/kg [Rabbit].
2) Methyl Ethyl Ketone	78-93-3	2.5-10	TWA: 200 (ppm) from OSHA (PEL) [United States] TWA: 200 STEL: 300 (ppb) from ACGIH (TLV) [United States] TWA: 590 STEL: 885 (ppm) from ACGIH (TLV) [United States] TWA: 200 STEL: 100	ORAL (LD50): Acute: 4050 mg/kg [Mouse]. 2737 mg/kg [Rat]. DERMAL (LD50): Acute: 6480 mg/kg [Rabbit].

Continued on Next Page

3) Glycol Ether PM Acetate	108-65-6	2.5-10	(ppm) from NIOSH TWA: 100 (ppm) from AIHA	ORAL (LD50): Acute: 8532 mg/kg [Rat].
4) Xylene	1330-20-7	10-25	TWA: 100 (ppm) from OSHA (PEL) [United States] TWA: 100 STEL: 150 (ppb) from ACGIH (TLV) [United States] TWA: 434 STEL: 651 (ppm) from ACGIH (TLV) [United States] TWA: 100 STEL: 150 (ppm) from NIOSH	ORAL (LD50): Acute: 4300 mg/kg [Rat]. DERMAL (LD50): Acute: 3950 mg/kg [Rabbit].

Section 3. Hazards Identification

Potential Acute Health Effects	Very hazardous in case of skin contact (irritant), of eye contact (irritant), of inhalation. Hazardous in case of skin contact (permeator), of ingestion. Inflammation of the eye is characterized by redness, watering, and itching. Skin inflammation is characterized by itching, scaling, reddening, or, occasionally, blistering.
Potential Chronic Health Effects	CARCINOGENIC EFFECTS: Classified A4 (Not classifiable for human or animal.) by ACGIH, 3 (Not classifiable for human.) by IARC [Toluene]. Classified A4 (Not classifiable for human or animal.) by ACGIH, 3 (Not classifiable for human.) by IARC [Xylene]. MUTAGENIC EFFECTS: Not available. TERATOGENIC EFFECTS: Not available. DEVELOPMENTAL TOXICITY: Not available. The substance is toxic to blood, kidneys, the nervous system, liver, gastrointestinal tract, upper respiratory tract, skin, eyes. Repeated or prolonged exposure to the substance can produce target organs damage.

Section 4. First Aid Measures

Eye Contact	Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Cold water may be used. Get medical attention immediately.
Skin Contact	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Cover the irritated skin with an emollient. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Ingestion	Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention if symptoms appear.

Section 5. Fire Fighting Measures

Products of Combustion	
Fire Fighting Media and Instructions	Flammable liquid, soluble or dispersed in water. SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use alcohol foam, water spray or fog.
Special Remarks on Fire Hazards	Vapor may travel considerable distance to source of ignition and flash back. (Xylene)

Continued on Next Page

Special Remarks on Explosion Hazards	Not available.
	Not available.
	Highly flammable in presence of open flames and sparks.


Section 6. Accidental Release Measures

Small Spill and Leak	Absorb with an inert material and put the spilled material in an appropriate waste disposal.
Large Spill and Leak	Flammable liquid. Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not touch spilled material. Prevent entry into sewers, basements or confined areas; dike if needed. Be careful that the product is not present at a concentration level above TLV. Check TLV on the MSDS and with local authorities.
Personal Protection in Case of a Large Spill	Splash goggles. Full suit. Vapor respirator. Boots. Gloves. A self-contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

Section 7. Handling and Storage

Precautions	Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapor/spray. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. Keep away from incompatibles such as oxidizing agents, reducing agents, organic materials, metals, alkalis.
Incompatibility	Reactive with oxidizing agents, reducing agents, organic materials, metals, alkalis. Slightly reactive to reactive with acids. Non-reactive with moisture.
Storage	Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).

Section 8. Exposure Controls/Personal Protection

Engineering Controls	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.
Personal Protection	
	<i>Eyes</i> Splash goggles.
	<i>Body</i> Lab coat.
	<i>Respiratory</i> Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Wear appropriate respirator when ventilation is inadequate.
	<i>Hands</i> Gloves.
Protective Clothing (Pictograms)	

Continued on Next Page

Exposure Limits**Toluene**

TWA: 200 (ppm) from OSHA (PEL) [United States]

TWA: 50 (ppb) from ACGIH (TLV) [United States]

TWA: 188 (ppm) from ACGIH

TWA: 100 STEL: 150 (ppm) from NIOSH

Glycol Ether PM Acetate

TWA: 100 (ppm) from AIHA

Xylene

TWA: 100 (ppm) from OSHA (PEL) [United States]

TWA: 100 STEL: 150 (ppb) from ACGIH (TLV) [United States]

TWA: 434 STEL: 651 (ppm) from ACGIH (TLV) [United States]

TWA: 100 STEL: 150 (ppm) from NIOSH

Consult local authorities for acceptable exposure limits.

Section 9. Physical and Chemical Properties

Physical State and Appearance	Liquid.	Odor	Not available.
Molecular Weight	Not applicable.	Taste	Not available.
pH (1% Soln/Water)	Not available.	Color	Not available.
Boiling/Condensation Point	The lowest known value is 110.6°C (231.1°F) (Toluene). Weighted average: 135.95°C (276.7°F)		
Melting/Freezing Point	May start to solidify at -94.5°C (-138.1°F) based on data for: Toluene.		
Critical Temperature	Not available.		
Instability Temperature	Not available.		
Specific Gravity	0.942		
Vapor Pressure	The highest known value is 7 kPa (@ 20°C) (Toluene). Weighted average: 1.54 kPa (@ 20°C)		
Vapor Density	The highest known value is 4.6 (Air = 1) (Glycol Ether PM Acetate). Weighted average: 3.74 (Air = 1)		
Volatility	66+-5% (v/v).		
Evaporation Rate	The highest known value is 2.24 (Toluene) Weighted average: 0.85 compared to Butyl acetate.		
Odor Threshold	The highest known value is 1.6 ppm (Toluene) Weighted average: 0.49 ppm		
Viscosity	Not available.		
LogK_{ow}	The product is more soluble in oil.		
Ionicity (in Water)	Not available.		
Dispersion Properties	See solubility in water, methanol, diethyl ether, n-octanol.		
Solubility	Easily soluble in methanol. Soluble in diethyl ether, n-octanol. Partially soluble in cold water. Very slightly soluble in hot water.		
The Product is:	Flammable.		
Auto-ignition Temperature	The lowest known value is 354°C (669.2°F) (Glycol Ether PM Acetate).		

Continued on Next Page

Flash Points	The lowest known value is CLOSED CUP: 7°C (44.6°F). (Tagliabue.). OPEN CUP: 12.78°C (55°F). (Cleveland). (Toluene)
Flammable Limits	The greatest known range is LOWER: 1.3% UPPER: 13.1% (Glycol Ether PM Acetate)
Fire Hazards in Presence of Various Substances	Highly flammable in presence of open flames and sparks, of heat, of combustible materials. Flammable in presence of oxidizing materials, of reducing materials. Non-flammable in presence of moisture.
Explosion Hazards in Presence of Various Substances	Risks of explosion of the product in presence of mechanical impact: Not available. Risks of explosion of the product in presence of static discharge: Not available.

Section 10. Stability and Reactivity Data

Stability	The product is stable.
Conditions of Instability	Not available.
Incompatibility with Various Substances	Reactive with oxidizing agents, reducing agents, organic materials, metals, alkalis. Slightly reactive to reactive with acids. Non-reactive with moisture.
Corrosivity	Non-corrosive in presence of glass.
Hazardous Decomposition Products	
Special Remarks on Reactivity	Not available.
Special Remarks on Corrosivity	Not available.

Section 11. Toxicological Information

Routes of Entry	Dermal contact. Eye contact. Inhalation. Ingestion.
Toxicity to Animals	Acute oral toxicity (LD50): 2600 mg/kg [Rat]. (Toluene). Acute dermal toxicity (LD50): 3950 mg/kg [Rabbit]. (Xylene).
Acute Effects on Humans	<p><i>Eyes</i> Very hazardous in case of eye contact (irritant). Inflammation of the eye is characterized by redness, watering, and itching.</p> <p><i>Skin</i> Sensitization of the product: Not available. Very hazardous in case of skin contact (irritant). Hazardous in case of skin contact (permeator). Skin inflammation is characterized by itching, scaling, reddening, or, occasionally, blistering.</p> <p><i>Inhalation</i> Very hazardous in case of inhalation.</p> <p><i>Ingestion</i> Hazardous in case of ingestion.</p>
Chronic Effects on Humans	<p>CARCINOGENIC EFFECTS: Classified A4 (Not classifiable for human or animal.) by ACGIH, 3 (Not classifiable for human.) by IARC [Toluene]. Classified A4 (Not classifiable for human or animal.) by ACGIH, 3 (Not classifiable for human.) by IARC [Xylene].</p> <p>MUTAGENIC EFFECTS: Not available.</p> <p>TERATOGENIC EFFECTS: Not available.</p> <p>DEVELOPMENTAL TOXICITY: Not available.</p> <p>The substance is toxic to blood, kidneys, the nervous system, liver, gastrointestinal tract, upper respiratory tract, skin, eyes. Repeated or prolonged exposure to the substance can produce target organs damage.</p>

Continued on Next Page

Special Remarks on Toxicity to Animals	Not available.
Special Remarks on Chronic Effects on Humans	Detected in maternal milk in human. Passes through the placental barrier in animal. Embryotoxic and/or foetotoxic in animal. (Xylene)
Special Remarks on Other Toxic Effects on Humans	Material is irritating to mucous membranes and upper respiratory tract. (Xylene)


Section 12. Ecological Information

Ecotoxicity	Not available.
BOD5 and COD	Not available.
Products of Biodegradation	
Toxicity of the Products of Biodegradation	
Special Remarks on the Products of Biodegradation	Not available.


Section 13. Disposal Considerations

Waste Information	Waste must be disposed of in accordance with federal, state and local environmental control regulations.
Waste Stream	Not available.

Section 14. Transport Information

TDG Classification	Class 3: Flammable liquid.	
PIN	Shipping name: Paint UN1263 PG: II	
Maritime Transportation	Not available.	
Special Provisions for Transport	Not available.	

Section 15. Other Regulatory Information and Pictograms

WHMIS (Classification)	Class B-2: Flammable liquid with a flash point lower than 37.8°C (100°F).	
Regulatory Lists	CEPA DSL: Toluene; Glycol Ether PM Acetate; Xylene Canadian NPRI: Toluene; Xylene	
Other Regulations	OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).	
Other Classifications	HCS (U.S.A.) Class: Flammable liquid having a flash point lower than 37.8°C (100°F). Class: Irritating substance. Class: Target organ effects.	

Continued on Next Page

USA Regulatory Lists	<p>California prop. 65: This product contains the following ingredients for which the State of California has found to cause birth defects which would require a warning under the statute: Toluene Pennsylvania RTK: Toluene; Xylene Florida: Toluene; Xylene Minnesota: Toluene; Xylene Michigan critical material: Toluene; Xylene Massachusetts RTK: Toluene; Xylene New Jersey: Toluene; Xylene TSCA 8(a) PAIR: Toluene; Glycol Ether PM Acetate; Xylene SARA 313 toxic chemical notification and release reporting: Toluene 6.25%; Xylene 37.5% CERCLA: Hazardous substances: Toluene: 1000 lbs. (453.6 kg); Xylene: 100 lbs. (45.36 kg);</p>
DSD (EEC)	<p>R11- Highly flammable. R38- Irritating to skin. R41- Risk of serious damage to eyes.</p>
International Regulations Lists	<p>No products were found.</p>


Hazardous Material Information System (U.S.A.)

Health	*	2
Flammability		3
Reactivity		0
Personal Protection		h

National Fire Protection Association (U.S.A.)



DOT (U.S.A) (Pictograms)



DSD (Europe) (Pictograms)



ADR (Europe) (Pictograms)



Section 16. Other Information

References Not available.

Other Special Considerations Not available.

Validated by Janet Sills on 1/03/2007.

Verified by Carole Lamothe.

Printed 1/03/2007.

Information Contact
 Antoni Coatings Inc.
 2910 Marleau Avenue
 P.O. Box 1236
 Cornwall, Ontario
 K6H 5V3

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.